



Verso R 1500 F C5

Nominal air flow according to ErP 2018, m ³ /h	1500
Nominal air flow according to ErP 2018, l/s	417
Electric air heater capacity, kW / Δt, °C	6/11,7
Supply voltage HE, V	3~400
Supply voltage HW, V	1~230
Maximal operating current HE, A	12,1
Maximal operating current HW, A	3,8
Power supply cable E, mm ²	5×2,5
Power supply cable W, mm ²	3×1,5
Electric power input of the fan drive at maximum flow rate, W	350
Noise power level, L _{WA} , dB(A)	46
Noise pressure level, L _{PA} , dB(A), (3 m)	37
Filters dimensions B×H×L, mm	472×402×96
Supply filter class	ePM1 60 (F7)
Exhaust filter class	ePM10 50 (M5)
Unit dimensions B×H×L, mm	1039×480×1796
Panel thickness, mm	45
Maintenance space, mm	660
Unit weight, kg	195



Performance

Verso R 1500 F with standard equipment



Temperature efficiency

	Winter					Summer		
Outside temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	13,2	14,8	15,7	16,7	17,7	22,6	23,6	24,6

Indoor +22 °C, 20 % RH


Hot water duct air heater *

	Winter		
Water temperature in/out, °C	80/60	70/50	60/40
Capacity, kW	4,9	4,9	4,9
Flow rate, dm ³ /h	213	212	211
Pressure drop, kPa	10,9	8,9	9
Temperature in/out, °C	13,2 / 22,0		
Maximal capacity, kW	13,8	11,3	8,7
Connection, "	½		


* Option

Shown as right (R1)

View from inspection side




Shown as left (L1)



Accessories

Closing damper	AGUJ-M-315+LF24/LM24
Silencer	ODA/EHA AGS-315-100-1200-M
	SUP/ETA AGS-315-100-900-M
Water heater	DH-315
PPU	PPU-HW-3R-15-1,6-W2
Water cooler	DCW-1,4-9
2-way valve	VVP47.20-4,0+SSF161.05HF
DX cooler	DCF-1,4-10
Cooling unit for ducted cooler	MOU-36HFN8a+KA8142

Mounting positions



ODA – outdoor intake

SUP – supply air

ETA – extract indoor

EHA – exhaust air